

Lector CCD de Códigos de Barras

SEYPOS®
SC6000



SPECIFICATIONS CHART

Operational

Optical Systems	1500 Pixel CCD sensor
CPU	32 bits
Interfaces	USB , USB-COM,RS-232

Scan Performance

Scan Speed	200 Scans/sec.
Resolution	4 mil (0.1mm)
Print Contrast	45% or more
Scan Angle	45°
Scan Width	80mm or more (PCS90%)
Scan Distance	0-30mm (PCS90% Code 39)

Symbologies

Code 39, Full ASCII Code 39, Code 32, Code 128,
Code 93, Code 11, Codabar/NW7, All UPC/EAN/JAN code
(EAN-13, EAN-8, UPC-A, UPC-E, EAN-128),
Interleave 2 of 5, STD 2 of 5, Industrial 2 of 5, matrix 2 of 5,
Chinese Postage Code, IATA, MSI/PLESSY,
Italian Pharmacy Code, Telepen. GS1 databar

Electrical

Input Voltage	5V DC $\pm 5\%$
Operation Current	100-120mA
Standby Current	50-60mA

Environmental

Operating Temperature	32°C to 105°C (0°C to 50°C)
Storage Temperature	-15°C to +140°C (-26°C to 60°C)
Humidity	10% to 90% RH
Drop	1.5M

Regularity of Compliance

CE and RoHs compliant 

SEYPOS®
Touch Scan Print