

SEYPOS®

Touch Scan Print

Monitor Táctil TM 519



Diseñado, desarrollado y construido para ofrecer las soluciones táctiles más rentables para una venta rápida en supermercados, bares, restaurantes, cafeterías....

Fiable, duradero y resistente a las salpicaduras de líquido con la firmeza justa de pantalla en el toque

Monitor táctil

Especificaciones técnicas TM519

Model	TM-519
Form factor	Desktop
Enclosure color	Black
Diagonal size	19.0"
Aspect ratio	4:3
Useful screen area	Horizontal: 376.32mm Vertical: 301.056mm
Touch Screen	5-Wire Resistive Touch Technology, Capacitive Option
Interface	USB, RS232, USB&RS232 Combo
Monitor dimensions (without stand)	Width: 431.5 mm Height: 379mm Depth: 64mm Dimensions vary with stand position and options selected
Native (optimal) resolution	1280 x 1024 @ 85 Hz 1024 x 768 @ 60, 65 Hz (Sun), 70 or 75 Hz 832 x 624 @ 75 Hz (Mac)
Other supported resolutions	800 x 600 @ 56, 60, 72 or 75 Hz 720 x 400 @ 0 Hz 640 x 480 @ 60, 66 Hz (Mac), 72 or 75 Hz 640 x 350 @ 70 Hz
Colors	16.7 million
Brightness(typical)	LCD panel: 250 nits ResistiveTouch: 200 nits
Response time - total (typical)	5 msec
Viewing angle (typical)	Horizontal: ±89° or 178° total
Contrast ratio (typical)	1000:1
Input video format	Analog VGA
Input video signal connector	D-Sub 15-Pin VGA type
Input frequency	Horizontal: 31.5-60.2 kHz Vertical: 56.3-75 Hz
Power supply	Internal AC, Optional external DC (power brick)
Input voltage	AC: 100-240 VAC, 50/60 Hz DC: +12VDC ±5%, 4.16A
Input connector	AC: IEC 60320 C6 DC: 2 mm pin diameter, 6.4 mm barrel diameter, 8.8 mm barrel length)
Power consumption (typical)	45 W(max)
Options	
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Humidity(noncondensing)	Operating: 20%-80% Storage: 10%-90%
N.W/G.W	6.14kg/9.45kg
Shipping box dimensions (W x D x H)	513mm x 180mm x 505mm
Warranty	2 years
Optional product coverage	Advance Unit Replacement program (North America only)
Backlight lamp life	Typical 30,000 hours to half brightness
MTBF	50,000 hours demonstrated
On-screen display (OSD)	Controls (side): menu, up, down, select, power Settings: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall Languages: English, German, Spanish, Japanese, French, Chinese Lockouts: power, user controls
Stand options	Removable
Mounting options	75 mm VESA mount
Sealing	Touchscreen sealed to bezel Touchscreen sealed to LCD
Other features	Security lock receptacle