



„The exclusive POS System

Specifications – P2500

- **Robust checkout system with resistive or PCAP touch monitor and stand**
- **Elegant design with bezel-free surface and aluminium housing**
- **Hospitality professional with IP64-protected front panel**
- **Efficient Intel processors at up to 2.7 GHz, and up to 8 GB RAM**

		P2500
System	CPU	Intel Celeron G1820TE (2.2GHz) Optional: Intel Pentium G3320TE (2.3GHz), Intel Core i3-4330TE (2.4GHz), Intel Core i5-4570TE (2.7GHz)
	System memory	4 GB DDR3 RAM (up to 8 GB)
	Chipset	Intel Haswell
	Compact Flash	CFast card support
	Hard disk drive	320 GB HDD, optional SSD
	Audio	On-board
	Housing	Aluminium
	Supported operating systems	Windows Embedded Standard 7, Windows POSReady 7, Windows Embedded 8.1 Industry Pro, Linux
Display	Graphics chip	Intel integrated
	LCD screen size	38.1cm (15")
	Maximum resolution	1,024 x 768 pixels
	Brightness	350 cd/m²
	Touch screen	5-wire resistive, Projected Capacitive (optional)
Interfaces	USB	2x USB 2.0; 2x USB 3.0
	Serial/COM	2x DB9, 1x RJ45
	Parallel	Available on demand
	LAN	1x RJ45 10/100/1000 Base-T
	VGA	1x
	PS/2	1x
	Cash drawer port	1x RJ11 (12 V)
	Audio	Line-out, mic-in, speaker
PSU	Power adapter	150 watts
Other	Dimensions (WxDxH)	323.6 x 264.2 x 368 mm
	Weight	9.6 kg
	Operating temperature	0 to 40 °C
	Certification	CE, FCC, RoHS, IP64 (front panel)
	Mount	VESA 100 mm
Options	Magnetic stripe reader	Choice of MSR (track 1, 2, 3), MSR + iButton reader, MSR + smart card reader + iButton reader, MSR + smart card reader + fingerprint reader
	Customer display	VFD, 2 x 20 characters, (integrated or as pole)
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") screen size
	Barcode scanner	1D- or 2D-barcode scanner (optional RFID capability)
	Waiter lock	iButton (optional RFID capability), Addimat (RS232)
	RFID	13.56 MHz (MIFARE), 125KHz
	Colours	Black, white
	UPS	Up to 1 hour battery back-up

Your Dealer