

# SPP-R300

## 3 inch Mobile Printer

Mobile POS  
/ Retail

Deliveries

Customer  
Service Center

Ticketing

# Handy yet Rugged



### Enhanced Convenience

- Compatible with smart devices including iPhone, iPad, and Android
- Place entire device on cradle for an effortless charge
- Versatile connectivity (WLAN, Bluetooth, etc.)
- One touch cover open and simple drop-in paper loading



### Improved Printing Performance

- Linerless label printing (optional)
- Easily switch from receipt to label printing
- Low-temp (-15°C) printing with an integrated temperature sensor
- Faster printing speeds of up to 100 mm/sec (Receipt)
- Enhanced printing of fonts, graphics, and barcode symbologies



### Mobile Field-Work Optimization

- Handy yet rugged design
- Water and dust resistant (IP54 with protective case)
- Long-lasting battery life
- Optional Integrated Card Reader (MSR)

**BIXOLON**<sup>®</sup>  
a Better Solution for your Business™

# SPP-R300

## 3 inch Mobile Printer

### Specifications

#### Printer Specifications

**Print Method**

Direct Thermal

**Print Speed**

Up to 100 mm/sec (Receipt)  
Up to 80 mm/sec (Linerless)  
12.5% pattern

**Print Resolution**

203 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End: Reflective sensor  
Paper Cover Open: Mechanical switch

#### Media Characteristics

**Media Type**

Receipt and Label, Linerless (optional)

**Media Width**

80 mm

**Media Roll Diameter**

Up to 50 mm

**Media Thickness**

0.07 ± 0.003 mm

**Supply Method**

Easy Paper Loading

#### Physical Characteristics

**Dimensions (W x L x D)**

110.0 x 162.0 x 58.3 mm  
(4.33 x 6.38 x 2.30 inch)

**Weight**

Including battery: 550 g (1.21 lbs.)  
Including MSR: 565 g (1.25 lbs.)  
Paper : 133 g (0.29 lbs.)

**Battery**

7.4 V Li-ion, 2,600 mAh, Rechargeable  
Charging time: Up to 4.0 hrs

#### Performance Characteristics

**Memory**

64 Mbit SDRAM, 32 Mbit FlashROM

**Interface**

USB V1.1 FS

**Serial**

Bluetooth V3.0 + EDR  
WLAN 802.11 b/g - WEP40/104, WPA1/2  
(PSK, EAP)

#### Environment Characteristics

**Temperature**

Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

**Humidity**

Operating: 10 ~ 80% RH

**Sealing**

IP54 (with protective case)

**Drop Spec**

1.5 m (5ft.)

#### Software

**Emulation**

BXL / POS

**Driver**

Windows Driver, OPOS Driver, JPOS Driver,  
Linux CUPS Driver

**SDK**

iOS SDK, Android SDK, Windows SDK,  
Symbian SDK

#### Fonts/Graphics/Symbologies

**Character Size**

Font A: 12 × 24 Font B: 9 × 17 Font C: 9 × 24  
KOR, CHN: 24 × 24

**Characters Per Line**

Font A: 48 Font B, C: 64  
KOR, CHN: 24

**Character Sets**

Alphanumeric: 95  
Expanded Graphics: 128 × 33 page  
International: 32

**Graphics**

Supporting user-defined fonts, graphics, formats,  
layouts, and logos

**Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128, EAN-8,  
EAN-13, ITF, UPC-A, UPC-E  
2D: Data Matrix, MaxiCode, PDF417, QR code

#### Accessories

**Standard**

Belt Strap, Battery Pack, Battery Charger,  
Power Cord, Paper

**Optional**

Case, Protective Case, Shoulder Strap,  
Single Battery Cradle, Quad Battery Charger,  
Vehicle Charger, Serial/USB Cable, Cleaning Pen

#### Integrated Card Reader (optional)

**MSR**

3 Track, DUKPT (optional),  
T-DES Certified (optional)

Chunicisha, Japan (2014),  
Whole Picture of the Printer Market



**Global No.1 Spot**  
in the Mobile Printer Market



BR-SRP-R300-EN-APR15-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

**BIXOLON®**

**BIXOLON Co., Ltd.**  
+82 (0) 31 218 5500  
sales@bixolon.com

**BIXOLON America Inc.**  
+1 858 764 4580  
sales@bixolonusa.com

**BIXOLON Europe GmbH**  
+49 211 68 78 54 0  
sales@bixolon.de

www.bixolon.com

