P2V-TouchScreen-15plus

High-End 15" LCD monitor

With our new "plus" series of high-quality, touch screen moni tors we offer you truly professional displays with an integrated touch screen whose high, first-class performance, sophisti cated construction and robust design will both impress and excite your customers. The exclusive use of brand components and the coordinated concept of diverse features and combination interfaces guarantee not only a wide array of applications, but above all impressed customers.



Specifications

Generel	Model	P2V-15 plus
	Colour	dark grey
	Dimensions	321.9 x 364 x 206.08 mm (H x W x D)
	Net Weight / Shipping Weight	5.0 kg / 7.9 kg
	Power Supply	AC Input 90 ~ 264 V / DC 12 V
	Power Consumption	Operating: 25W (typ.) / Sleep: 4W / Off: 2W
	Montage Option	Stand / 75 x 75mm VESA Mount
Display	LCD Size / Type	15 Inch TFT Active Matrix Panel
	Active Area	304 x 228 mm (H x V)
	Pixel Pitch	0.297 x 0.297 mm (H x V)
	Panel Resolutions	1.024 x 768 Pixel
	Display Mode	VGA 720 x 400 (70Hz),
	Display Colour	16.2 Millionen Colour
	Contrast	500:1
	Brightness	without touch 250 nits / SAW 230 nits / Capacitive 212 nits / Resistive 200 nits
	Response Time	Tr: 2 ms / Tf: 6 ms
	Viewing Angle	Horizontal: $70^{\circ} \sim -70^{\circ}$ / Vertical: $65^{\circ} \sim -60^{\circ}$
	Video Input Format	RGB Analog 0.7 peak to peak
	Video Sync Format	Separated H&V Sync. / Composite Sync. / Sync-on Green
	Video Input Frequenz	Horizontal: 31Khz \sim 60.2 kHz / Vertikal: 56 Hz \sim 76 Hz
	Video Signal Input	D.sub 15 pin Female (analog)
Enviroment	Temperature - Operating	0°C ~ +40°C
	Temperatur - Storage	-20°C ~ +60°C
	Control Key	Power On/Off, select, down, up, Menu
ŭ	Audio	1W Speaker / 2 Channels





