## P2V-TouchScreen-19plus

## Professional high-end monitor

The P2V19plus rounds out the series of professional touch screens from P2V with the familiar first-class, high performance. The 19-inch monitor with a display size of 48.3 cm provides your custo mers with adequate space for extensive applications, diverse me nus and the most diverse functions. The integrated touch screen processes information precisely and quickly. Elegant design com bined with a robust and stable construction also awaits you in the 19-inch version. The P2V19plus comes exclusively with brand-name components, which offers your customers the security of long-term, defect-free use. Whether you use it in retail, production, the office or at information terminals, the high performance and high quality will excite your customers.



## **Specifications**

Generel	Model	P2V-19 plus
	Colour	dark grey
	Dimensions	405.5 x 438 x 267.4 mm ( H x W x D)
	Net Weight / Shipping Weight	9.9 kg / 12 kg
	Power Supply	AC Input 90 ~ 264 V / DC 12 V
	Power Consumption	Operating: 42W (typ.) / Sleep: 4W / Off: 2W
	Montage Option	Stand / 100 x 100mm VESA Mount
Enviroment Display	LCD Size / Type	19 Inch TFT Active Matrix Panel
	Active Area	376 x 301 mm (H x V)
	Pixel Pitch	0.294 x 0.294 mm ( H x V)
	Panel Resolutions	1.280 x 1.024 Pixel
	Display Mode	VGA 720 x 400 (70Hz),
	Display Colour	16.7 Millionen Colour
	Contrast	800:1
	Brightness	without touch 300 nits / SAW 270 nits / Capacitive 255 nits / Resistive 240 nits
	Response Time	Tr: 2 ms / Tf: 6 ms
	Viewing Angle	Horizontal: 80° ~ -80° / Vertical: 80° ~ -80°
	Video Input Format	RGB Analog 0.7 peak to peak
	Video Sync Format	Separated H&V Sync. / Composite Sync. / Sync-on Green
	Video Input Frequenz	Horizontal: 31Khz ~ 81 kHz / Vertikal: 56 Hz ~ 76 Hz
	Video Signal Input	D.sub 15 pin Female (analog)
	Temperature - Operating	0°C ~ +40°C
	Temperatur - Storage	-20°C ~ +60°C
	Control Key	Power On/Off, select, down, up, Menu
	Audio	1W Speaker / 2 Channels







