



POINT2VENTE.COM
EQUIPEZ VOTRE COMMERCE EN LIGNE



**5 years
warranty**

Specifications

Printing Method	Direct Thermal
Equipment	Autocutter, two connections for cash drawers, Paper Near End/End Sensor
Colour	Black or White
Printing Speed	150 mm/s
Roll Changes	Easy Paper Drop-In (single-handed and without contriving)
Resolution	7 Dot/mm (180 dpi)
Character Set	Alphanumeric: 96 characters
Extended Graphic	128 x 7 pages (1 space page)
Character Size	Size: Font A: 12 x 24, Font B: 9 x 17; per line: Font A: 42, Font B: 56
Consumables	Thermal paper
Paper	Width: max. 83 mm, core: max. 19 mm
Durability	100 km TPH (direct thermal printhead), 1,5 million cuts (Autocutter)
Flash Memory	16 Mbit
Memory for logos	256 KB (NV RAM)
Barcodes	EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda bar, UPC-A, UPC-E
Emulation	ESC/POS
Driver	Windows 95/98/Me/2000/NT/XP/2003 Server, OPOS
Sensors	Paper end, paper near end, wall mounting near end, cover open
Memory	8 KB printer buffer, 256 KB memory for logos (NV RAM)
Interfaces	RS232C, parallel, USB; Ethernet, DUAL (serial/USB) optional
Options	Wallmount
Power supply	AC120V-230V +/- 10 %, DC24V, 2,3A
Dimensions (mm)	145 (W) x 195 (L) x 146 (H)
Warranty	60 months