

OKIPOS® 410



Impresora de tickets térmica. Velocidad de 150mm/seg (47LPS)
 Resolución de 203 dpi. Corte de papel automático.
 Imprime logotipos y códigos de barras.
 Disponible en blanco y negro. Conexión cajón portamonedas.

CARACTERISTICAS PRINCIPALES OKIPOS 410

PRINT	PRINT METHOD	Direct Thermal
	PRINT SPEED	150 mm/ sec (47.2 LPS)
	PAPER SUPPLY METHOD	Easy Paper Loading
	RESOLUTION	180 dpi (7dot/mm)
	CHARACTER SET	Alphanumeric Character : 96 Extended Graphic : 128 X 7 page (1space page) International Character : 32
PAPER ROLL	CHARACTER SIZE	Font A : 12 X 24, Font B: 9 X 17
	CHARACTER PER LINE	Font A : 42, Font B : 56
	PAPER TYPE	Thermal paper
	WIDTH	79.5 mm ± 0.5 mm
	DIAMETER	Max. Ø 83.0 mm
RELIABILITY	MCBF	37,000,000 Lines
	AUTO CUTTER	1.5 million cuts
	TPH	100,000,000 pulse, 100Km
BARCODES		EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda bar, UPC-A, UPC-E
EMULATION		ESC/POS
FLASH MEMORY		16 Mbit
DRIVER		Windows95/98/Me/2000/NT/XP/2003/OPOS, USB
SENSOR		Paper Near End Sensor, Paper End Sensor
DRAWER PORT		2 Port
CONNECTIVITY	INTERFACE	RS-232C, IEEE1284, USB, RS-485, Ethernet
OPTIONS	LANGUAGE	Buyer language support
	WALL MOUNT	RWM-350
POWER	SUPPLY	AC120V~230V ± 10% (Include), DC24V, 2.3A
DIMENSION		145(W) × 195(L) × 146(H) mm
OPERATING TEMP.		0 ~ 45°C
AUTO CUTTER	TYPE	Guillotine (1,500,000 Cuts)

